

Item no. 53064600-01

FM-TL646
Draka Coax3 CT 33 A(3.45/14.9)

Frequency Range 0.3 - 3000 MHz
Impedance (Nom.) 75 Ω
(calculated) 6.0 A @10°C increase
8.4 A @20°C increase

Product photo



Transfer Impedance (CoMeT) Class A+
<2.5 mΩ/m @ 5-30MHz

Screening Attenuation(CoMeT) Class A++
>105 dB @ 30-1000MHz
>105 dB @ 1000-2000MHz
>105 dB @ 2000-3000MHz

Return Loss (IEC 61169-1)	Better than	Typical
0.3 - 500 MHz	-35 dB	-38.4 dB
500 - 860 MHz	-35 dB	-38.4 dB
860 - 1000 MHz	-35 dB	-38.4 dB
1000 - 1750 MHz	-35 dB	-38.4 dB
1750 - 2150 MHz	-35 dB	-38.4 dB
2150 - 3000 MHz	-33 dB	-35.4 dB

Insertion Loss Max.	Better than	Typical
0.3 - 500 MHz	-0.06 dB	-0.01 dB
500 - 860 MHz	-0.07 dB	-0.02 dB
860 - 1000 MHz	-0.07 dB	-0.02 dB
1000 - 1750 MHz	-0.09 dB	-0.04 dB
1750 - 2150 MHz	-0.09 dB	-0.04 dB
2150 - 3000 MHz	-0.09 dB	-0.04 dB

Temperature
Installing -5° to +50° C
Operating -40° to +70° C
Storing -40° to +70° C

Intermodulation IM3
3rd Order (@2x+30dBm) -135 dBc

Inner Conductor Resistance (@ 1 A DC) <1.0 mΩ

Sealing Test (IEC IP-code) IP X8 30 meter / 8 hours

Insulation Resistance (@ 500 VDC) >200 GΩ

O-rings EPDM

Dielectric Strength DC Test Voltage >2.0 KV

Base Material
Body Parts Brass CuZn39Pb3
Inner Conductor Brass CuZn39Pb3

Max. Tensile Strength
Overall >1500 N
Inner Conductor >500 N

Plating
Body Parts Nitin-6
Inner Conductor Nitin-6

Torsional Strength (Connector / Cable) * NATM

Insulators COC (Topas) / PP with Glass

Test performed by Sven-Erik Sandberg
Date of release July 09, 2014

Remarks * Not Able To Measure(NATM): The cable starts to twist without the connector losing its grip.

*All tests performed using instruments calibrated in accordance to our ISO 9001 certification.
Further technical specifications and installation instructions can be obtained on request.*