

Item no. 31000309-01

SP TL309  
Draka Coax4 CT22 A (2,2/9,3/12,5)

Frequency Range 0.3 - 3000 MHz  
Impedance (Nom.) 75 Ω  
(calculated) 19.0 A @10°C increase  
26.8 A @20°C increase

Product photo



Transfer Impedance (CoMeT) Class B  
\* <7.4 mΩ/m @ 5-30MHz  
<0.64 mΩ/item @ 5-30MHz

Screening Attenuation(CoMeT) Class B  
>80 dB @ 30-1000MHz  
>75 dB @ 1000-2000MHz  
>75 dB @ 2000-3000MHz

Return Loss (IEC 61169-1)	Better than	Typical
0.3 - 500 MHz	-43 dB	-46.0 dB
500 - 860 MHz	-40 dB	-42.9 dB
860 - 1000 MHz	-39 dB	-41.8 dB
1000 - 1750 MHz	-34 dB	-37.5 dB
1750 - 2150 MHz	-28 dB	-30.7 dB
2150 - 3000 MHz	-20 dB	-22.4 dB

Insertion Loss Max.	Better than	Typical
0.3 - 500 MHz	-0.09 dB	-0.04 dB
500 - 860 MHz	-0.13 dB	-0.08 dB
860 - 1000 MHz	-0.14 dB	-0.09 dB
1000 - 1750 MHz	-0.17 dB	-0.12 dB
1750 - 2150 MHz	-0.22 dB	-0.17 dB
2150 - 3000 MHz	-0.30 dB	-0.25 dB

Temperature  
Installing -5° to +50° C  
Operating -40° to +70° C  
Storing -40° to +70° C

Intermodulation IM3  
3rd Order (@2x+30dBm) -130 dBc

Inner Conductor Resistance (@ 1 A DC) <0.6 mΩ

Sealing Test (IEC IP-code) IP X8 30 meter / 8 hours

Insulation Resistance (@ 500 VDC) >200 GΩ

O-rings EPDM

Dielectric Strength DC Test Voltage >3.5 KV

Base Material  
Body Parts Brass CuZn39Pb3  
Inner Conductor Brass CuZn39Pb3

Max. Tensile Strength  
Overall >720 N  
Inner Conductor >245 N

Plating  
Body Parts Nitin-6  
Inner Conductor Nitin-6

Torsional Strength (Connector / Cable) >2.5 Nm

Insulators COC (Topas) / PP with Glass

Test performed by Sven-Erik Sandberg  
Date of release December 05, 2014

Remarks \* The low Transfer Impedance and Screening is caused by the cable used.  
\*\*Not Able To Measure(NATM): The cable starts to twist without the connector loosing its grip.

*All tests performed using instruments calibrated in accordance to our ISO 9001 certification.  
Further technical specifications and installation instructions can be obtained on request.*