

Item no. 33004000-01

SR TL101-TL303  
Draka Coax 9 AD 11 S  
CommScope CL 2.1 / 8.8

For cable 2

**Frequency Range** 0.3 - 3000 MHz  
**Impedance (Nom.)** 75 Ω  
(calculated) 9.5 A @10°C increase  
13.4 A @20°C increase

Product photo



**Transfer Impedance (CoMeT)** Class A+  
<2.5 mΩ/m @ 5-30MHz

**Screening Attenuation(CoMeT)** Class A++  
>130 dB @ 30-1000MHz  
>125 dB @ 1000-2000MHz  
>125 dB @ 2000-3000MHz

Return Loss (IEC 61169-1)	Better than	Typical
0.3 - 500 MHz	-33 dB	-35.5 dB
500 - 860 MHz	-27 dB	-30.4 dB
860 - 1000 MHz	-26 dB	-28.4 dB
1000 - 1750 MHz	-19 dB	-21.4 dB
1750 - 2150 MHz	-16 dB	-19.4 dB
2150 - 3000 MHz	-15 dB	-17.8 dB

Insertion Loss Max.	Better than	Typical
0.3 - 500 MHz	-0.07 dB	-0.02 dB
500 - 860 MHz	-0.08 dB	-0.03 dB
860 - 1000 MHz	-0.08 dB	-0.03 dB
1000 - 1750 MHz	-0.13 dB	-0.08 dB
1750 - 2150 MHz	-0.16 dB	-0.11 dB
2150 - 3000 MHz	-0.23 dB	-0.18 dB

**Temperature**  
Installing -5° to +50° C  
Operating -40° to +70° C  
Storing -40° to +70° C

**Intermodulation** IM3  
3rd Order (@2x+27dBm) -135 dBc

**Inner Conductor Resistance**  
(@ 1 A DC) <3.5 mΩ

**Sealing Test**  
(IEC IP-code) IP X8 30 meter / 8 hours

**Insulation Resistance**  
(@ 500 VDC) >200 GΩ

**O-rings** EPDM

**Dielectric Strength**  
DC Test Voltage >2.5 KV

**Base Material**  
Body Parts Brass CuZn39Pb3  
Inner Conductor Brass CuZn39Pb3 / Beryllium copper

**Max. Tensile Strength**  
Overall >18.3 Kgf  
>180 N

**Plating**  
Body Parts Nitin-6  
Inner Conductor Nitin-6

**Torsional Strength**  
(Connector / Cable) \* NATM

**Insulators** COC (Topas) / PP with Glass

**Test performed by** Søren B. Sørensen  
**Date of release** January 04, 2015

**Remarks** \* Not Able To Measure(NATM): The cable starts to twist without the connector losing its grip.

*All tests performed using instruments calibrated in accordance to our ISO 9001 certification.  
Further technical specifications and installation instructions can be obtained on request.*