

tv-outlets



Data sheet

Type	Freja IM0-H	Euro IM0-H	Odin IM0-H
Complete coax outlet Item no. white	52110	52120	52130
Version	Terminated Transparent		
Screws, Claws and elastics band included	Yes		-
IEC Male			
Frequency forward/reverse	5 - 1218 MHz		
Insertion loss	5-204MHz	< 0.3 dB	
	204-862MHz	< 0.4 dB	
	862-1218MHz	<0.7 dB	
Return loss	IEC 60728-4 5.3.4.2		
DC Block	100V		
Connector	IEC-Male EN61169-2		
Input			
Return loss (5-1218 MHz)	IEC 60728-4 §5.3.4.2		
Cable center conductor diameter	0.41 - 1.13 mm		
	Center conductor	7mm	
	Dielectric	2mm	
	Braid	9mm	
	Jacket	3.5 - 8 mm	
Common			
Screening effective-ness	5 - 30 MHz	> 90 dB	
	30 - 300 MHz	> 85 dB	
	300 - 470 MHz	> 80 dB	
	470 - 1218 MHz	> 75 dB	
Operating temperature	0°C - 55°C		
Max dimensions (HxWxD)	76,2x50x27,7mm	81x81x38mm	66,5x65,5x39,5mm
Metal Housing	RoHS compliant Zink alloy		
Face plate material	ABS	ABS	ABS
Included Face plates			
White	Type	FFP-IM0	EFP-IM0
	Item number	52112	52122
Not-Included Face plates - sold separately			
Light grey	Type	FFP-IM0-G	OFP-IM0-G
	Item Number	52113	52133
Antracite	Type	FFP-IM0-KG	OFP-IM0-KG
	Item Number	52114	52134
Included wall mounting box			
White	Type	-	UBH
	Item number	-	52808
Included frame			
White	50 mm	-	1 module 66