

WISI DY 70

Wall wart 230 V AC, 13 V DC



Description

The DY 70 is a short circuit-proofed power supply operating at an input voltage of 230 V AC, 50/60 Hz and provides an output voltage of 13 V DC. It is used in combination with multiswitches of the PROSWITCH series, as well as the amplifier DY 40 and surge protector DL 400.

At a glance:

- Ensures the power supply of the LNB
- For use with DY multi-switches, DY amplifiers or the overvoltage protection DL 400

Technical data

General data

F-plug	1 pcs.
Input voltage	100240 V AC (50/60 Hz)
Operating range	90...264 V AC (50/60 Hz)
Output voltage	13 V DC
Max. output current	2.3 A
Max. output power	<30 W
Average operational efficiency	86.9 %
Low load efficiency (10%)	76.2 %
Max. humidity, non condensing	90 %
Protection class	II
Protection class system EN 60529 (DIN 40050)	IP 41
Electrical safety standard	EN 60065, EN 60950
EMC	EN 50083-2
Dimensions W x H x D	72,2 x 42,2 x 68,2 mm
Operating temperature range	-20...+40 °C
Storage temperature	-20...+80 °C

Packaging data

Sales unit	1 pcs.
Dimensions (WxHxD) sales unit	95 x 80 x 60 mm
Packaging volume sales unit	dm ³
Gross weight sales unit	235 kg
Shipping unit	pcs.
Dimensions (WxHxD) shipping unit	mm
Packaging volume shipping package	dm ³
Gross weight shipping unit	kg
EAN	4010056765743
Article number	76574
Customs tariff number	85044090