

# CC-3-TPE-F-S+

20193 | F-jumper cable

## PRODUCT OVERVIEW

Parameter	FREQUENCY [MHZ]	CC-3-TPE-F-S+
<b>Test specification (DIN EN 60966-2-6)</b>		
Characteristic impedance [Ohm]	200	75 ±3
Return loss [dB]	5 - 1000	≥20
	1000 - 2000	≥18
	2000 - 3000	≥16
Attenuation [dB] (maximum values dB/100 m)	50	10.4
	450	32.1
	1000	40.8
	2050	60.1
	3000	74.1
Screening Class [dB] Class A+	30 - 1000	≥95
	1000 - 2000	≥85
	2000 - 3000	≥75
Transfer impedance [MΩ/m]	5 - 30	2.5
<b>Material</b>		
Inner conductor	-	Oxygen-free copper (OFC)
Inner insulation	-	Low density polyethylene (LDPE)
Shield 1	-	Bonded Al Foil 0.053 mm
Shield 2	-	Braid 64/0.12 mm Oxygen-free copper (OFC)
Shield 3	-	Doublesided Al Foil 0.053 mm
Shield 4	-	Braid 32/0.12 mm Oxygen-free copper (OFC)
Jacket	-	White (RAL9003) Low Smoke Zero Halogen Low density polyethylene
<b>Dimensions</b>		
Length [mm]	-	3000 ± 20
Packaging [mm] (W x L)	-	200 x 220
<b>Item No.</b>		<b>20193</b>

Dimensions in mm

