


tv-outlets

Preliminary - Subject to change
Data sheet



Type	Freja IM0-H	Euro IM0-H	Odin IM0-H	
Terminated Transparent				
Complete coax outlet Item no. white	52110	52120	52130	
Version				
Terminated Transparent				
Screws, Claws and elastics band included				
Yes				
IEC Male				
Frequency forward/reverse				
5 - 1218 MHz				
Insertion loss	5-118MHz	< 0.1 (± 0.1) dB		
	118-125MHz	< 0.2 (± 0.2) dB		
	1006-1218MHz	<0.3 (± 0.2) dB		
Return loss				
IEC 60728-4 5.3.4.2				
DC Block				
100V				
Connector				
IEC-Male EN61169-2				
Input				
Return loss (5-1218 MHz)				
IEC 60728-4 5.3.4.2				
Cable center conductor diameter				
0.41 - 1.13 mm				
Cable stripping instruction				
			TBD - inset drawing	
Cable outer Jacket diameter				
3.5 - 8 mm				
Common				
Screening effective-ness	5 - 30 MHz	> 90 dB		
	30 - 300 MHz	> 85 dB		
	300 - 470 MHz	> 80 dB		
	470 - 1218 MHz	> 75 dB		
Operating temperature				
0 °C - 55 °C				
Max dimensions (HxWxD)				
TBD		TBD	TBD	
Metal Housing				
RoHS compliant Zink alloy				
Face plate material				
TBD		TBD	TBD	
Included Face plates				
White	Type	FFP-IM0	EFP-IM0	OFP-IM0
	Item number	52112	52122	52132
Not-Included Face plates - sold separately				
Light grey	Type	FFP-IM0-G	-	OFP-IM0-G
	Item Number	52113	-	52133
Antracite	Type	FFP-IM0-KG	-	OFP-IM0-KG
	Item Number	52114	-	52134
Included wall mounting box				
White	Type	-	UBH	-
	Item number	-	52808	-
Included frame				
White	50 mm	-	1 module 66	