



## Wi-Fi ACCESS POINTS

### FUNKTIONER

Wi-Fi Standarder

Antal samtidige klienter

Netværks Interfaces

PoE/PoE+

2,4GHz hastighed

5 GHz hastighed

Antal SSID's

Antal Antenner

Miljø

WiFi og System sikkerhed

### GWN7615

### GWN7630

### GWN7660

### GWN7664

### GWN7630LR

IEEE 802.11a/b/g/n/ac

IEEE 802.11a/b/g/n/ac

IEEE 802.11a/b/g/n/ac/ax

IEEE 802.11a/b/g/n/ac/ax

IEEE 802.11a/b/g/n/ac

200+

200+

250+

450

200+

2x autosensing 10/100/1000  
Base-T Ethernet ports

2x autosensing 10/100/1000  
Base-T Ethernet ports

2x autosensing 10/100/1000  
Base-T Ethernet port

1x 1G Port og 1x2,5G Port  
Support for 3,5Gbps aggregate

2x autosensing 10/100/1000  
Base-T Ethernet ports

PoE 802.3af/802.3at  
Max power: 12,5W

PoE 802.3af/802.3at  
Max power: 16,5W

PoE 802.3af/802.3at  
Max power: 9W

PoE 802.3af/802.3at  
Max power: 17W

PoE 802.3af/802.3at  
Max power: 16,5W

450Mb/s  
(3x3:3 MIMO)

600Mb/s  
(4x4:4 MIMO)

573,5Mb/s  
(2x2:2 MIMO)

1147Mb/s  
(4x4:4 MIMO)

600Mb/s  
(4x4:4 MIMO)

1300Mb/s  
(3x3:3 MU-MIMO)

1733Mb/s  
(4x4:4 MU-MIMO)

1201Mb/s  
(2x2:2 MU-MIMO)

2402Mb/s  
(4x4:4 MU-MIMO)

1733Mb/s  
(4x4:4 MU-MIMO)

32 total 16 pr Radio  
(2,4GHz og 5GHz)

32 total 16 pr Radio  
(2,4GHz og 5GHz)

32 total 16 pr Radio

32 total 16 pr

32 total 16 pr Radio  
(2,4GHz og 5GHz)

3x dual band  
intern antenne

4x dual band  
intern antenne

2x dual band  
intern antenne

4x dual band  
intern antenne

4x dual band  
Ekstern antenne

Indendørs

Indendørs

Indendørs

Indendørs

Udendørs

WEP, WPA/WPA2-PSK, WPA/WPA2  
Enterprise (TKIP/AES); WPA3, anti-  
hacking secure boot and critical data/

WEP, WPA/WPA2-PSK, WPA/WPA2  
Enterprise (TKIP/AES); WPA3, anti-  
hacking secure boot and critical data/  
control lockdown via digital signatures.

WEP, WPA/WPA2-PSK,  
WPA/WPA2 Enterprise (TKIP/AES);  
WPA3, anti-hacking secure boot  
and critical data/ control lockdown  
via digital signatures, unique  
security certificate and random

WEP, WPA/WPA2-PSK,  
WPA/WPA2 Enterprise (TKIP/AES);  
WPA3, anti-hacking secure boot  
and critical data/ control lockdown  
via digital signatures, unique  
security certificate and random

WEP, WPA/WPA2-PSK, WPA/WPA2  
Enterprise (TKIP/AES); WPA3, anti-hacking  
secure boot and critical data/ control  
lockdown via digital signatures.

Management

GWN Cloud  
GWN Manager  
Indbygget controller

GWN Cloud  
GWN Manager  
Indbygget controller

GWN Cloud  
GWN Manager  
Indbygget controller

GWN Cloud  
GWN Manager  
Indbygget controller

GWN Cloud  
GWN Manager  
Indbygget controller

Montering

Loft/væg montage

Loft/væg montage

Loft/væg montage

Loft/væg montage

Monter på Rør/Beslag

Dimensioner

205,4x205,4x45,9

205,4x205,4x45,9

180,4x180,4x40,8

205,4x205,4x45,9

533,1x115x40

VLAN support

Ja

Ja

Ja

Ja

Ja

Dæknings radius med fuld båndbredde 5GHz \*

10m

10m

7m

7m

10m

\*Det vil sige at Access point 802.11AC skal placeres med 20 meters afstand og Access point 802.11AX med 15 meters afstand, for at opnå fuld båndbredde. Lofts højde max 3 meter. Afstandene kan godt være større, men med dette medfører lavere båndbredde.