

WISI OH 85 H

Twin DVB-S/S2 – QAM transmodulator with CI



Description

Powerful technology, compact dimensions, modular and flexibly expandable; the WISI COMPACT HEADEND System OH combines all the advantages of an innovative and affordable headend. WISI Compact Headend OH is easy to configure. With up to 14 module slots it offers channel processing for 14 analogue or 28 digital channels in a 3 HU 19" rack chassis. WISI Compact Headend OH operates on a high efficiency power supply, with low consumption modules in order to make a minimum ecological impact and a low operational cost. The USB connection and the RJ45 interface can be used to execute software updates for the basic unit as well as for the modules. Furthermore, all functions can be furnished from a distance per web browser.

At a glance:

- Reception of two DVB-S/S2-signals and transmodulation into two DVB-C channels
- 2 CI-interfaces
- Input frequency range 950–2150 MHz
- Output frequency range 47–862 MHz
- MPEG 2 and MPEG 4 compatible
- PID filtering
- NIT and LCN generation

WISI Communications GmbH & Co. KG

Wilhelm-Sihn-Str. 5-7
75223 Niefern-Oeschelbronn, Germany

Phone: +49 7233 66-280, Fax: -350
E-Mail: export@wisi.de

Technical Modifications reserved. WISI cannot be held liable for any printing error. 19. Dezember 2016, 12:05 nachm.

Technical data

Input

Input frequency range	950...2150 MHz
Input frequency steps	1 MHz
Input level range	47...70 dBμV
AFC	±10 MHz
Modulation	QPSK, 8PSK
Symbol rate	10...30 Mbaud
Spectral inversion	normal or inverted
FEC outer DVB-S	RS 204, 188, 16
FEC inner DVB-S	Conv. 1/2, 2/3, 3/4, 5/6, 7/8
FEC outer DVB-S2	BCH
FEC inner DVB-S2	LDPC 1/2, 3/5, 2/3, 3/4, 4/5, 5/6, 8/9, 9/10

Output

Output frequency range	110...862 MHz
Output frequency steps	1000 kHz
Frequency stability	±30 MHz
Output channel bandwidth (couple)	2 x 8 MHz
Output level	85...103 dBμV
Amplitude response (O-E)	1 dB
Modulation type	16-, 32-, 64-, 128-, 256- QAM
Symbol rate	3.45...6.9 MS/s
Spurious suppression	>50 dB
SNR	≥45 dB
MER	≥40 dB
Bit stuffing	Yes
PCR correction	Yes
PID filtering	Yes
LCN	Yes
NIT generation	Yes

Connectors

F-socket	3 pcs.
Common Interface	2 pcs.

General data

Power consumption	<10 W
LNB supply voltage	14/18 V (22 kHz), DiSEqC 1.0
LNB electrical power supply	0.5 A (without CAM)
Dimensions (width x height x depth)	29,5 x 105 x 253 mm
Operating temperature range	-20...+55 °C

Packaging data

Sales unit	1 pcs.
Dimensions (WxHxD) sales unit	325 x 150 x 55 mm
Packaging volume sales unit	dm³
Gross weight sales unit	0.587 kg
Shipping unit	pcs.
Dimensions (WxHxD) shipping unit	mm
Packaging volume shipping package	2.681 dm³
Gross weight shipping unit	0.587 kg
EAN	4010056740429
Article number	74042
Customs tariff number	85437090